

DF2.5S - Portable Outboard

Small in Size, Big in Performance

SPECIFICATIONS

Model	DF2.5
Engine Type	Water-cooled 4 stroke OHV
Fuel Delivery System	Carburetor
Shaft Length mm	S:381 mm
Starting System	Manual
Weight kg	13kg
No.of Cylinders	1
Piston Displacement cm3	68cm3
Bore x Stroke mm	48 x 38 mm
Maximum output kW (	1.8 kw
Full Throttle Operation Range rpm	5250-5750
Steering	Tiller
Fuel Tank Capacity l	Integral 1.0
Oil Pan Capacity in l	0.3
Ignition System	Pointless Electronic Ignition
Engine Mounting	Bushing Type
Trim Method	Manual
Gear Ratio	2.15:1
Gear Shift	F-N
Exhaust	Above Prop Exhaust
Propeller Size (in.)	7 3/8 x 5 3/8

Meets the rigorous EPA2006 and CARB 3-Star Ultra Low emissions standards



DF2.5S

PRODUCT INFORMATION



DF2.5S - Portable Outboard

Small in Size, Big in Performance

The DF2.5S is the Lightest Suzuki 4-stroke motor built and generates plenty of power for small tenders and inflatables.

Engine

- Pointless Electronic Ignition - easy-to-pull recoil starting
- Powerful power generation for small inflatables and tenders
- No battery required
- Simple and reliable
- Quiet and Smooth operation
- Water-cooled system promoting dependability
- 1 hour run time on a full tank
- Oil level indicator - easy check of oil levels



2.5HP single Cylinder OHV 4-stroke with 68cm3

Handling

- Full size Grip - positive throttle control
- Upper bushing in collar - promotes smooth steady steering
- Adjustable steering and throttle tension
- F-N Shifting
- 360 degree steering



Twist-grip throttle and full-turn 360 steering



Tilt and Carry Handle

- Easy-to-grip integrated handle
- Cowling within convenient reach
- Four tilt pin settings - match boat and prevailing conditions
- Fuel On/Off switch
- Balanced, lightweight, easy to manage

Lightweight

- Easy transport and storage
- Weight - 13.5 kg
- Easy operation
- Easy maintenance

